

SAFETY DATA SHEET

Section 1. Product Identification

Product identifier	Dynaplast® Base Alpha, Dynaplast® Alpha Q/S, Dynaplast® Alpha Q/S Buff, Dynaplast® HS, Dynaplast® FS, Dynaplast® GRG Gypsum Cement, Dynaplast® GRG XL, Dynaplast® OCG 60, Dynaplast® OCG 120, Dynaplast® DS712, Dynaplast® DS712 Buff,
Other means of identification	
SDS number	ACG 2001
Additional Products	Pottery Plaster , Moulding Plaster, Moulding Plaster S/S, 15 min Moulding Plaster, 20 min Moulding Plaster, 30 min Moulding Plaster, Quick-Set Plaster of Paris, Slow-Set Plaster of Paris, Lab Dental Plaster Q/S, and Dental Plaster 1530.
Synonyms	Plaster of Paris
Recommended use	Ceramics and modeling.
Recommended Restrictions	Use in accordance with manufacturer's recommendations.
Manufacturer/Importer/Supplier/Distributor information	
Company name	ACG Materials
Address	1550 Double Drive Norman, OK 73069
Telephone	1-800-624-5963
Website	www.ACGmaterials.com
Emergency phone number	1-800-624-5963

Section 2. Hazard(s) Identification

Emergency Overview	This product is not flammable, combustible, or explosive. It does not cause burns or severe skin or eye irritation. A single exposure will not result in serious adverse health effect. Prolonged contact with the product may result in abrasions to the skin or irritation of the eyes. Prolonged inhalation of the dust may irritate the respiratory tract.
Physical hazards	Not classified
Health Hazards	Not classified
Acute:	
Eyes	Contact can cause mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician. Eye irritation Category 2, subcategory 2B.
Skin	This material hardens and slowly become shot when mixed with water. However, direct prolonged or repeated contact with the skin may cause irritation. Rubbing of this product against the skin can result in abrasions. Rinse with water until free of material to avoid abrasions, and then wash skin thoroughly with mild soap and water. May dry skin. Mild Skin Irritation Category B. Inhalation of dusts from this product may irritate the nose, throat, lungs, and upper respiratory tract. Persons exposed to large amounts of this dust may be forced to leave area because of nuisance conditions such as coughing, sneezing, and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician.
Ingestion	Harmful if swallowed. Plaster of Paris is non-toxic, however, ingestion of a sufficient quantity could lead to mechanical obstruction of the gut, especially the pyloric region. See Section 4.
Chronic:	
Inhalation	Gypsum displays no specific toxic properties. Prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer. Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica.
Skin	Dermatitis.

**Environmental hazards
OSHA defined hazards**

 Not Classified.
Not Classified.

Label elements

Signal word

Danger

Hazard statement

Harmful if swallowed. Causes eye and skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statement
Prevention

Avoid breathing dust. Wash hands thoroughly after handling. Wear protective gloves. Wear respiratory protection. Do not eat, drink, or smoke when using this product. Contact lenses should not be worn while working with Plaster of Paris.

Response

If eye irritation persists, if skin irritation occurs, or if experiencing respiratory symptoms: Get medical advice/attention. If swallowed: Call a doctor if you feel unwell.

Storage

Store as indicated in Section 7.

Disposal

Dispose of in accordance with local, state, and federal regulations.

**Hazard(s) not otherwise
classified (HNOC)**

None known.

Section 3. Composition/Information on Ingredients
Mixtures

Chemical name	CAS number	%
Calcium Sulfate Hemihydrate (Plaster of Paris)	26499-65-0	>95
Silicon Dioxide (Crystalline Silica)	14808-60-7	<0.025

Composition comments

All concentrations are in percent by weight unless ingredient is a gas.

Section 4. First-Aid Measures
Eye contact

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

If on skin: Wash with plenty of water/mild soap and water. Specific treatment: see supplemental first aid instruction on label. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Inhalation

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a doctor.

Ingestion

If swallowed: Call a doctor if you feel unwell. Rinse mouth. Unlikely to occur, but may cause gastric disturbances if swallowed. Plaster of Paris is non-toxic; however, ingestion of a sufficient quantity could lead to mechanical obstruction of the gut, especially the pyloric region. Get medical attention immediately. The use of diluents is controversial and neutralization is contraindicated.

Target Organs:

Eyes, skin and respiratory system.

**Medical Conditions which
may be aggravated**

Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema, and asthma.

Primary Routes of entry:

Inhalation, eyes and/or skin contact, ingestion.

Section 5. Fire and Explosion Hazard Data
Flash Point

Non-combustible

Auto-Ignition	Not applicable.
Flammable limit	Not applicable.
Fire Extinguishing Media	Use extinguishing media appropriate for surrounding fire.
Special Fire-fighting Procedures	Wear proper personal protective equipment as listed in Section 8.
Hazardous combustion procedures	Not applicable.
Explosion Hazards	None known.

Section 6. Accidental Release Measures

Methods and materials for containment and cleaning up	Remove by dry sweeping or vacuum. Avoid creating excessive dust. It is recommended that gloves and a mask be worn while cleaning the spill. If already mixed with water, scrape up and place in container. Wear appropriate protective equipment as described in Sections 7 & 8.
Environmental precautions	Dispose of material in accordance with all applicable federal, state and local regulations. Can be disposed as an inert solid in a landfill. Slurry may plug drains.

Section 7. Handling and Storage

Precautions for safe handling	Avoid contact with skin and eyes. Do not breathe dust. Use only in well ventilated areas. Wear appropriate eye and respiratory protection, including a NIOSH approved dust mask, if dust is generated. When using, do not eat or drink. Wash hands before eating, drinking or smoking.
Conditions for safe storage, including an incompatibilities	Keep out of reach of children. Keep the container tightly closed and dry. Store in a covered, dry climate controlled area, away from incompatibles listed in Section 10.

Section 8. Exposure Controls/Personal Protection

Occupational exposure limits US. OSHA table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Plaster of Paris	PEL	5 mg/m ³	Respirable.
Crystalline Silica	TWA	5 mg/m ³	Respirable

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Plaster of Paris	TWA	10 mg/m ³	Inhalable fraction.
Crystalline Silica	TWA	0.025 mg/m ³	Respirable.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Plaster of Paris	TWA	5 mg/m ³	Respirable
Crystalline Silica	TWA	.05 mg/m ³	Respirable

Engineering Controls Ventilate to keep exposures below TLV requirements of the individual ingredients. General ventilation is expected to be satisfactory, Use local exhaust ventilation if necessary to control dust.

Respiratory protection None required where adequate ventilation conditions exist. In order to meet TLV requirements of individual ingredients and to control dusting conditions, provide general ventilation and local exhaust ventilation. Avoid creating dust. Wear a NIOSH/MSHA approved dust respirator in poorly ventilated areas and/or if TLV requirements of the individual ingredients is exceeded.

Section 9. Physical and Chemical Properties

Appearance White



Physical state	Powder/Solid.
Melting Point	Not applicable.
Freezing Point	Not applicable.
Odor	Low.
Odor threshold	Not determined.
Flash point	Non-combustible.
Flammability limits	Not applicable.
Solubility (in water) (g/100g)	0.15%
Initial boiling point	Not applicable
Boiling Range	Not applicable.
Specific gravity	2.6-3.0
pH	8
Hardening time	25-120 minutes
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Auto-ignition temperature	None.
Evaporation rate	Not applicable.
Viscosity	Not applicable.
Upper flammability limit	Not determined.
Lower flammability limit	Not determined.
Decomposition temp	1451°C/2642°F

Section 10. Chemical Stability and Reactivity

Conditions of reactivity	Reacts with water and produces large amounts of heat (normal condition of use).
Chemical stability	Stable at normal storage conditions and temperature.
Conditions to avoid	Water, high humidity, and acids.
Hazardous decomposition products	Stable at normal storage conditions and temperature.
Hazardous polymerization	None known.

Section 11. Toxicological Information

Information on likely routes of exposure

Acute effects	The acute oral toxicity study [OECD TG 420] of calcium sulfate dihydrate showed that this chemical did not cause any changes and there was no evidence of germ cell mutagenicity.
Chronic effects	Crystalline Silica: Exposures to respirable crystalline silica are not expected during the normal use of this product; however, levels must be determined by in-house workplace hygiene testing.

Section 12. Ecological Information

Ecotoxicity	There are no known causes from this product that would harm the Ecology.
-------------	--

Section 13 Disposal Considerations

Disposal procedure	Dispose of material in accordance with all applicable federal, state and local regulations. Can be disposed as an inert solid in a landfill. Slurry may plug drains. Do not dispose of directly in waterways or sewers.
--------------------	---

Section 14. Transport Information

Department of Transportation (DOT)	This product is not regulated as a hazardous material by the United States (DOT)
------------------------------------	--

Requirements	transportation regulations.
Canadian Transportation of dangerous goods	Not regulated as dangerous goods.
UN#	None, Not regulated as dangerous goods.
ADNR	None.
RID/ADR:	Not classified.
Environmental hazards	None.
Annex II of MARPOL 73/78	Not applicable.
International bulk chemical code	Not applicable.

Section 15 Regulatory Information

U.S. EPA's Toxic Substance Control Act Chemical Substance Inventory	Not listed as reportable quantity or regulated quantity in SARA Title III Sections 302, 304, and 313. CAA Section 112® Regulated Chemicals for Accidental Release Prevention, CERLA Hazardous Substances, and RCRA Hazardous Waste.
Canadian Controlled Product Regulations	Crystalline Silica: IDL* Item #1406 Classification: D2A
European Union Directive 67/548/EEC (Annex III and IV)	R36, R37, R38, S37, S3, S39, and S51.

*IDL Item: Canadian Hazardous Product Act Ingredient Disclosure List
 ** WHMIS: Workplace Hazardous Safety Information System

Section 16 Other Information


16. Other Information, including date of preparation or last revision

Issue date	01-June 2015
Version #	03

Further information NFPA Ratings “
 Health: 1
 Flammability: 0
 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.